

type number: **KPS 160X150_PO** width (A) = 280 mm
KPS 160X200_PO width (A) = 330 mm
KPS 160X300_PO width (A) = 430 mm
KPS 160X400_PO width (A) = 530 mm

product description: KPS cable clamp cover is fixed on the base material (concrete, solid brickwork) and creates thermal protection of the clamps, which in that way may perform its mechanical function even in fire conditions. The cover is fixed using ZT 8 threaded rods, M 8 nuts and PVL 8 washers anchored using KPOZ 8 anchors (MS KPS kit) to the base material. KPS cover is not classified as the fire-stop plug. If the cover is to perform safely its function, it must be installed on ascending routes consisting of cable ladders by max. 3.5 m. The cover is positioned symmetrically with the cable ladder cross-piece with cable clamps PKC1

KPS cover includes calcium-silicate fire protection boards, insulation wool and a cartridge with insulation cement.

The installation kit MS KPS (not included) must be ordered to attach the cover to the base material.

The installation kit contains fire-resistant anchors, threaded rod, washers, nuts and a knife for cutting heat-insulating wool.

MS KPS is being sold separately

sales amount: á 1 pc

classification: ČSN 73 0895 P 60-R
 DIN 4102-12 E 60
 STN 92 0205 PS 60

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

