



product description: designed for distribution system with voltage 400 V and with maximum current 16 A
 intended for devices of Classic and Swing - ABB series
 suitable for devices with great mounting depth
 on the sides of the box are marked inlets for the trunkings
 to install on materials with fire classes E or F, use insulating pad

material: PVC
 color: white / imitation pink birch / imitation dark oak / light brown
 self-snuffing: yes, within 30 s
 temperature resistance: -5 - +60 °C
 flaming loop test: 850 °C
 fire class for underlying material: A1-D
 weight: 46 g
 meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21
 storage: ČSN 64 0090

LK 80X28R/1_HB - 10 pcs of boxes including device screws packed in foil; 120 pcs of boxes in carton; color - white
 LK 80X28R/1_I1 - 10 pcs of boxes including device screws packed in foil; 120 pcs of boxes in carton; color - imitation pink birch
 LK 80X28R/1_I2 - 10 pcs of boxes including device screws packed in foil; 120 pcs of boxes in carton; color - imitation dark oak
 LK 80X28R/1_SD - 10 pcs of boxes including device screws packed in foil; 120 pcs of boxes in carton; color - light brown

accessories: screwless terminal plates TYP015, TYP016, TYP017, TYP018
 cover VLK 80/R
 extending frame NR 80/R
 thermo-isolating pad PI 80R
 terminal plate S-66

