

type number	A mm	for width of cable tray mm	thickness of metal sheet mm	max. load kg	weight kg/pc
<b>NP 100_S</b>	100	50	1,2	100	0,06
<b>NP 150_S</b>	150	100	1,2	100	0,08
<b>NP 200_S</b>	200	150	1,2	100	0,11
<b>NP 250_S</b>	250	200	1,2	100	0,14
<b>NP 300_S</b>	300	250	1,2	100	0,17
<b>NP 350_S</b>	350	300	1,2	100	0,20
<b>NP 100_ZM</b>	100	50	1,2	100	0,06
<b>NP 150_ZM</b>	150	100	1,2	100	0,08
<b>NP 200_ZM</b>	200	150	1,2	100	0,11
<b>NP 250_ZM</b>	250	200	1,2	100	0,14
<b>NP 300_ZM</b>	300	250	1,2	100	0,17
<b>NP 350_ZM</b>	350	300	1,2	100	0,20



product description:

The load bearing profile is intended as a support for the installation of cable ladders or trays. The load bearing profile is fixed by using two threaded rods ZT 8 + nut M 8 + washer PD 8.

The size of the load bearing profile is determined according to the width of the cable tray or cable ladder + 50 mm, for example for a cable tray that is 100 mm wide, order NP 150.

ZM surface finish load bearing profile shall be used for ZM or F surface finish trays.

These items can also be ordered in a varnished version.

surface finish:

S - Pre-Galvanized steel according to ČSN EN 10346, ČSN EN 10143, zinc-layer 15-27 µm

ZM - Pre-Galvanized steel with admixture of magnesium and aluminum according to ČSN EN 10346, ČSN EN 10143, protective layer 18-31 µm (replacement of hot dip galvanizing)

sales amount:

á 1 pc

meets the requirements:

ČSN EN 61537:02

classification

ČSN 73 0895 P 90-R  
DIN 4102-12 E 90  
STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

Product approved for standard and non-standard constructions.

storage:

ČSN EN 60721-3-1

