

# ELEKTROTECHNICKÝ ZKUŠEBNÍ ÚSTAV



ELECTROTECHNICAL TESTING INSTITUTE - CZECH REPUBLIC  
ELEKTROTECHNISCHE PRÜFANSTALT - TSCHECHISCHE REPUBLIK  
INSTITUT ELECTROTECHNIQUE D'ESSAIS - RÉPUBLIQUE TCHÉQUE  
ЭЛЕКТРОТЕХНИЧЕСКИЙ ИСПЫТАТЕЛЬНЫЙ ИНСТИТУТ - ЧЕШСКАЯ РЕСПУБЛИКА

Pod lisem 129/2, Troja, 182 00 Praha 8

## CERTIFICATE

No.: 2110073

Ordering firm: KOPOS KOLÍN a.s.  
Havlíčkova 432, Kolín IV , 280 02 Kolín, Czech Republic

Manufacturer/Licence holder: KOPOS KOLÍN a.s.  
Havlíčkova 432, Kolín IV , 280 02 Kolín, Czech Republic

Production site: KOPOS KOLÍN a.s.  
Havlíčkova 432, Kolín IV , 280 02 Kolín, Czech Republic

Name of product: Electroinstallation pliable conduit LPE - x (series EN) and accessories

Trade name:

Type of product: 2316E/LPE-1 to 2363/LPE-1  
2316E/LPE-2 to 2363/LPE-2  
(see Annex)

Rating: -25 °C to +90 °C, spreading flame material, for installation up to 1000 V AC

Electrotechnical Testing Institute on the basis of fulfillment the requirements of the „ESČ Mark” certification scheme is granting a licence for using the following mark



This mark may be used for the product specified in this certificate within validity of the Agreement on the use of the ESČ Mark by implementing all the rules stated in the Agreement.

The right to use the above mentioned mark for the product is based on:

- Test report No. 104917-01/01 of: 09.12.2011

A sample of the product was tested and found to be in conformity with:

ČSN EN 61386-1ed.2:09, ČSN EN 61386-22:04, (IEC 61386-1:2008, IEC 61386-22:2002)  
TP-KO-02-11, TP-KO-03-11

- inspection at manufacturing site according to Permanent Documents CIG 023 and CIG 024 No. 104674-01 of: 11.08.2011
- the Agreement on the use of the ESČ Mark No. 104917 concluded between the ordering firm and the Electrotechnical Testing Institute

Other data:

23.12.2011 Corr. 18.04.2024

Prague

Mgr. Miroslav Sedláček  
Head of Certification Body



Stamp



\* C E R / 2 1 1 0 0 7 3 \*

104917-01

**Elektroinstalační trubky ohebné LPE-x (řada EN) a příslušenství**  
**Electroinstallation pliable conduit LPE-x (series EN) and accessories**

**(-25°C až +90°C) / (-25°C to +90°C)**

ČSN EN 61386-1 ed.2 (IEC 61386-1)  
 ČSN EN 61386-22 (IEC 61386-22)

**Elektroinstalační trubky typ: / Electroinstallation pliable type:**

| TP-KO-02/11<br>320 N | TP-KO-03/11<br>125 N |
|----------------------|----------------------|
| 2316 E/ LPE-1        | 2316 E/ LPE-2        |
| 2320 / LPE-1         | 2320 / LPE-2         |
| 2325 / LPE-1         | 2325 / LPE-2         |
| 2332 / LPE-1         | 2332 / LPE-2         |
| 2340 / LPE-1         | 2340 / LPE-2         |
| 2350 / LPE-1         | 2350 / LPE-2         |
| 2363 / LPE-1         | 2363 / LPE-2         |

|  |                         |
|--|-------------------------|
| <b>spojky / couplers:</b>  | <b>0216E/1 – 0263/1</b> |
| <b>ucpávky do trubek / pliable plug</b>  | <b>1716E T - 1763 T</b> |
| <b>ucpávky do spojek / joint plug</b>  | <b>1716E S - 1763 S</b> |
| <b>přechodové spojky z dimenze 20 na 16</b><br>transition couplers from dimension 20 on 16     | <b>0206E/1</b>          |
| <b>přechodové spojky z dimenze 20 na 2x16</b><br>transition couplers from dimension 20 on 2x16 | <b>0207E/1</b>          |
| <b>protahovací drát / pull-out wire</b>  | <b>D</b>                |

18.04.2024

