

type number: **QP 45X45 C**

item number: QP 45X45 C_HB - white

QP 45X45 C_BB - red

QP 45X45 C_FB - black

for wires: 1,5-2,5 mm² Cu

fasten the wire: with screws

rated voltage: 250 V AC

rated current: 16 A

IP-protection: IP20

material: PC - ABS

dimension (width x height): 45 x 45 mm

dimension (depth): 38 mm

weight: 39 g/pc

certification: ČSN IEC 60884-1

storage: ČSN 64 0090

installation: by click only

sockets can be connect continuously, trunkings or boxes determine

max. number of sockets

recommended tightening torque 0,6 Nm

suitable for: parapet trunkings

PK 90X55 D, PK 120X55 D, PK 160X65 D, PK 170X65 D, PK 210X70 D

floor boxes

KOPOBOX 57, KOPOBOX 80

multi-purpose boxes

KOPOBOX mini

description: the shutters physically block access to live contacts and only allow the plug to be Inserted when even pressure is applied to both openings at the same time



recycling codes:



plastic parts of the socket



other parts of the socket



carton



foil

WARNING

Incorrect electrical installation can cause a fire - we recommend the connection to be carried out exclusively by an authorized person.
Product damage - if the socket module is visibly damaged, stop using it.

Follow the manufacturer's installation instructions according to the installation instructions, videos.

Under normal and foreseeable conditions of use, the installed socket module does not pose any risks to consumers.